



## Your Partner In Fire Safety

Product Approval



**FIRE INDO****FIRE INDO****Portable****Dry Chemical Powder**
**ABC**  
 Kelas Api

| Type                         | FI- 10 P           | FI - 20 P | FI - 30 P | FI - 50 P | FI - 60 P | FI - 90 P | FI - 12 P |
|------------------------------|--------------------|-----------|-----------|-----------|-----------|-----------|-----------|
| Kapasitas                    | 1 Kg               | 2 Kg      | 3 Kg      | 5 Kg      | 6 Kg      | 9 Kg      | 12 Kg     |
| Tinggi Tabung                | 29 cm              | 37 cm     | 41 cm     | 50 cm     | 56 cm     | 57 cm     | 66 cm     |
| Diameter                     | 15 cm              | 17,5 cm   | 21 cm     | 22,5 cm   | 24 cm     | 27,5 cm   | 31 cm     |
| Working Pressure             | 15 - 18 Bar        |           |           |           |           |           |           |
| Test Pressure                | 27 Bar             |           |           |           |           |           |           |
| Berat Keseluruhan            | 1,97 Kg            | 3,24 Kg   | 5,71 Kg   | 7,56 Kg   | 9,23 Kg   | 12,68 Kg  | 18,27 Kg  |
| Fire Rating (Lab. Dinas PMK) | 2A - 10B           | 3A - 15B  | 4A - 30B  | 6A - 30B  | 7A - 40B  | 10A - 60B | 13A - 70B |
| Efektifitas Penyemprotan (%) | 95%                | 95%       | 95%       | 95%       | 95%       | 95%       | 95%       |
| Jarak Penyemprotan (m)       | 2 - 7m             | 2 - 8m    | 2 - 9m    | 3 - 11m   | 3 - 12m   | 4 - 14m   | 4 - 14m   |
| Efektifitas Pemadaman        | 5 > 10 Detik       |           |           |           |           |           |           |
| Temperatur                   | 20°C > 60°C        |           |           |           |           |           |           |
| Finishing                    | STICKER ANTI ROBEK |           |           |           |           |           |           |

**FIRE INDO****Trolley****Dry Chemical Powder**
**ABC**  
 Kelas Api

| Type                         | FI - 200 P         | FI - 500 P | FI - 750 P | FI - 1500 P | FI - 2000 P |
|------------------------------|--------------------|------------|------------|-------------|-------------|
| Kapasitas                    | 20 Kg              | 50 Kg      | 75 Kg      | 150 Kg      | 200 Kg      |
| Tinggi Tabung                | 98 cm              | 85 cm      | 130 cm     | 110 cm      | 120 cm      |
| Diameter                     | 24 cm              | 31,5 cm    | 34 cm      | 54 cm       | 60 cm       |
| Working Pressure             | 15 - 18 Bar        |            |            |             |             |
| Test Pressure                | 27 Bar             |            |            |             |             |
| Berat Keseluruhan            | 65 Kg              | 100 Kg     | 132 Kg     | 160 Kg      | 540 Kg      |
| Fire Rating (Lab. Dinas PMK) | 2A - 120B          | 30A - 125B | N/A        | N/A         | N/A         |
| Efektifitas Penyemprotan (%) | 85%                | 85%        | 85%        | 85%         | 85%         |
| Jarak Penyemprotan (m)       | 6m                 | 7m         | 8m         | 9m          | 10m         |
| Efektifitas Pemadaman        | 5 > 10 Detik       |            |            |             |             |
| Temperatur                   | 20°C > 60°C        |            |            |             |             |
| Finishing                    | STICKER ANTI ROBEK |            |            |             |             |



ISO / SNI ISO 9001:2008 Certified

**PT. Global Mitra Proteksindo**  
 Fire Protection and Safety Equipment

Dynamic Company's Management System has been Certified to ISO / SNI ISO 9001:2008

**FIRE INDO****FIRE INDO***Portable & Trolley***FOAM AFFF 6%****Kelas Api**

| Type                         | FI- 40 F           | FI - 60 F | FI - 90 F | FI - 120 F | FI - 200 F | FI - 500 F |
|------------------------------|--------------------|-----------|-----------|------------|------------|------------|
| Kapasitas                    | 4 Ltr              | 6 Ltr     | 9 Ltr     | 12 Ltr     | 20 Ltr     | 50 Ltr     |
| Tinggi Tabung                | 50 cm              | 56 cm     | 57 cm     | 66 cm      | 98 cm      | 85 cm      |
| Diameter                     | 22,5 cm            | 24 cm     | 27,5 cm   | 31 cm      | 24 cm      | 31,5 cm    |
| Working Pressure             | 15 - 18 Bar        |           |           |            |            |            |
| Test Pressure                | 27 Bar             |           |           |            |            |            |
| Berat Keseluruhan            | 7,56 Kg            | 9,23 Kg   | 12,68 Kg  | 18,27 Kg   | 65 Kg      | 100 Kg     |
| Fire Rating (Lab. Dinas PMK) | 6A - 30B           | 7A - 40B  | 10A - 60B | 13A - 70B  | 2A - 120B  | 10A - 60B  |
| Efektifitas Penyemprotan (%) | 95%                | 95%       | 95%       | 95%        | 85%        | 85%        |
| Jarak Penyemprotan (m)       | 3 - 11m            | 3 - 12m   | 4 - 14m   | 4 - 14m    | 6m         | 7m         |
| Efektifitas Pemadaman        | 5 > 10 Detik       |           |           |            |            |            |
| Temperatur                   | 20°C > 60°C        |           |           |            |            |            |
| Finishing                    | STICKER ANTI ROBEK |           |           |            |            |            |

**FIRE INDO***Portable & Trolley***Carbon Dioxide (CO<sup>2</sup>)****Kelas Api**

| Type                         | FI - 230 C         | FI - 320 C | FI - 460 C | FI - 680 C | FI - 2300 C | FI - 4500 C |
|------------------------------|--------------------|------------|------------|------------|-------------|-------------|
| Kapasitas                    | 2,3 Kg             | 3,2 Kg     | 4,6 Kg     | 6,8 Kg     | 23 Kg       | 45 Kg       |
| Tinggi Tabung                | 54 cm              | 73,5 cm    | 72,5 cm    | 90 cm      | 153 cm      | 164 cm      |
| Diameter                     | 17 cm              | 19,2 cm    | 40 cm      | 31 cm      | 22 cm       | 26 cm       |
| Working Pressure             | 20 - 30 Bar        |            |            |            |             |             |
| Test Pressure                | 40 Bar             |            |            |            |             |             |
| Berat Keseluruhan            | 6,8 Kg             | 9,5 Kg     | 16 Kg      | 25 Kg      | 98,5 Kg     | 147,5 Kg    |
| Fire Rating (Lab. Dinas PMK) | 2B                 | 3B         | 3B         | 4B         | 7B          | 10B         |
| Efektifitas Penyemprotan (%) | 96%                | 96%        | 97%        | 97%        | 90%         | 90%         |
| Jarak Penyemprotan (m)       | 3 - 6m             | 3 - 6m     | 4 - 7m     | 4 - 7m     | 7m          | 8m          |
| Efektifitas Pemadaman        | 5 > 10 Detik       |            |            |            |             |             |
| Temperatur                   | 20°C > 60°C        |            |            |            |             |             |
| Finishing                    | STICKER ANTI ROBEK |            |            |            |             |             |



ISO / SNI ISO 9001:2008 Certified

**PT. Global Mitra Proteksindo**

Fire Protection and Safety Equipment

Dynamic Company's Management System has been Certified to ISO / SNI ISO 9001:2008



**GMP**  
GLOBAL MITRA PROTEKSINDO

## ALAT PEMADAM API SERBAGUNA

1. Alat Pemadam berkualitas dan harga termurah
2. Di sertifikasi Lab Dinas Pemadam Kebakaran DKI Jakarta (No. 489/-1.784.25)
3. Tersedia dalam semua ukuran baik ringan maupun besar
4. Tersedia dalam jenis Powder, Foam, Co2 dan Liquid Gas
5. Dapat mematikan api dalam kelas A, B, & C

***FIRE INDO***



PT. Globalm Mitra Proteksindo  
Komp. Perkantoran Taman Palem Mutiara  
Blok A15 No. 28 Cengkareng, Jakarta Barat  
Telp : 021 - 54353513, 54353488, 54353498  
Fax : 021 - 54355904  
Email : [sales@globalmitraproteksindo.com](mailto:sales@globalmitraproteksindo.com)  
Website : [www.globalmitraproteksindo.com](http://www.globalmitraproteksindo.com)



ISO / SNI ISO 9001:2008 Certified

PT. Global Mitra Proteksindo  
Fire Protection and Safety Equipment

Dynamic Company's Management System has been Certified to ISO / SNI ISO 9001:2008